



DR.SCHNELL

SC Anti-Graffiti-System

Full impact. Zero compromise!

Graffiti removal.

The highly effective DR.SCHNELL SC Anti-Graffiti-System

Buses, trains, truck tarps – large surfaces attract graffiti artists, causing millions in damage each year. Tough demands make graffiti removal a particular challenge. Spray paint needs to be removed without a trace from the exterior while preserving the vehicle paint and material.

Inside, where markers or fibre-tip pens stain surfaces and upholstery, special cleaners are required that evaporate

quickly and without odour. All of our graffiti removal products are free from NMP/NEP and orange terpenes (significantly reduces risk of allergy).

More
information





SC GEL

Gel-based, low-odour graffiti remover



Field of Application

SC GEL is ideally suited for removing graffiti caused by spray paints and paint or felt-tip markers from all smooth and porous surfaces, indoors and outdoors. Thanks to its excellent adhesion, SC GEL is particularly suitable for cleaning vertical surfaces. The gel consistency results in extremely low product consumption and a strong, targeted effect thanks to a long dwell time on vertical surfaces. Suitable for cleaning vehicles and buildings.

Product Properties

- **NMP-/NEP- and VOC-free (i.e. no volatile solvents)**
- Free of orange terpenes (significantly reduces the risk of allergies)
- Viscous product formulation ensures good adhesion, even on vertical surfaces, and prevents product aerosols
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Completely odourless
- Handy 500 ml bottle for mobile cleaning on the go
- The oval shape of the 10 kg bucket means no decanting is required before treating large areas
- Consumption approx. 150 ml/m²
- **Listed and approved in accordance with DB standard RIL 910**
- Ready to use

Application

Apply SC GEL undiluted, evenly and generously. Monitor the dissolving process. Once the dissolving process has begun, work on the graffiti with suitable mechanical means if necessary. Thoroughly remove the dissolved paint. The surface can then be given a follow-up clean with SC FLÜSSIG, SC FASSADEN GEL or SC SCHATTEN to dissolve any remaining paint residue. Dry sensitive surfaces, such as paintwork, with absorbent cloths or similar after cleaning to prevent damage from prolonged exposure to the cleaning solution. Repeat the process as necessary until the desired result is achieved.

Notes

Before each application, test material compatibility in an inconspicuous area. During summer use, high surface temperatures can occur, particularly on vehicles. In this case, SC GEL may dry quickly, but can be reactivated for further use with SC FLÜSSIG. **The product contains renewable raw materials** – colour variations are normal and have no effect on its fitness for use.

Box of 6 x 500 ml bottles | Order No. 00584

5 L canister | Order No. 30585

10 L bucket | Order No. 30579

SC FLÜSSIG

Liquid, low-odour graffiti remover



Field of Application

For graffiti removal indoors and outdoors. For removing spray paint as well as paint and felt-tip marker residue from all smooth and porous surfaces. Ready to use.

Product Properties

- **NMP-/NEP- and VOC-free (i.e. no volatile solvents)**
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Completely odourless
- Handy 500 ml bottle for mobile cleaning on the go
- Consumption approx. 150 ml/m²
- **Listed and approved in accordance with DB standard RIL 910**
- Ready to use

Application

Apply SC FLÜSSIG undiluted and evenly. Monitor the dissolving process. Absorb or wash off the dissolved paint immediately. Rinse thoroughly with water. Dry sensitive surfaces, such as paintwork, with absorbent cloths or similar to prevent damage from subsequent exposure to the cleaning solution. Repeat the process as necessary until the desired result is achieved.

Notes

Before each application, test material compatibility in an inconspicuous area. **The product contains renewable raw materials** – colour variations are normal and have no effect on its fitness for use.

Box of 6 x 500 ml bottles | Order No. 00589

5 L canister | Order No. 30588

10 L canister | Order No. 30587



SC BITUMEN

Bitumen remover



Field of Application

For removing paints/contamination based on tar/bitumen, e.g. spray paint or underbody protection. (Tar and bitumen can be identified by their softer consistency and brownish discolouration when dissolving.) Suitable for cleaning vehicles and buildings.

Product Properties

- NMP-/NEP- and VOC-free (i.e. no volatile solvents)
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Based on coconut oils
- Consumption approx. 150 ml/m²
- Listed and approved in accordance with DB standard RIL 910
- Ready to use

Application

Apply SC BITUMEN undiluted and evenly. Monitor the dissolving process. Once the dissolving process has begun, work on the graffiti with suitable mechanical means if necessary. Thoroughly remove the dissolved paint immediately. As a final step, rinse the cleaned surface with a diluted, mildly alkaline cleaning solution (e.g. PUROL or CLEANMOTION WERKSTATT-REINIGER). Dry sensitive surfaces, such as paintwork, with absorbent cloths or similar after cleaning to prevent damage from subsequent exposure to the cleaner. Repeat the process as necessary until the desired result is achieved.

Notes

Before each application, test material compatibility in an inconspicuous area. **The product contains renewable raw materials** – colour variations are normal and have no effect on its fitness for use. For mixed graffiti contamination (e.g. bitumen and acrylic paints), SC GEL and SC FLÜSSIG can be applied wet-on-wet to areas already treated with SC BITUMEN.

5 L canister | Order No. 30583

SC SCHATTEN

Shadow remover



Field of Application

Suitable for graffiti removal indoors and outdoors. Specially designed to dissolve old, stubborn paint residue from absorbent and porous surfaces following the use of SC GEL or SC FLÜSSIG. SC SCHATTEN can be applied directly after using other products from the SC Anti-Graffiti System, with no need for intermediate cleaning.

Product Properties

- NMP-/NEP-free
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Extremely strong dissolving power
- Consumption approx. 150 ml/m²
- Listed and approved in accordance with DB standard RIL 910
- Ready to use

Application

Apply SC SCHATTEN concentrated and evenly, and allow to work under constant observation. Monitor the dissolving process. The cleaner acts extremely quickly! The effect can be further enhanced by using suitable mechanical means. Remove the dissolved paint residue immediately and rinse thoroughly with plenty of water. Repeat this process until the residue is completely removed. Dry sensitive surfaces, such as paintwork, with absorbent cloths or similar to prevent damage from exposure to the cleaning solution. Repeat the process as necessary until the desired result is achieved.

Shadow removal: After application, apply the graffiti remover to the still-damp substrate and allow to work. Rinse thoroughly with water. Dry sensitive surfaces (e.g. paintwork) with absorbent cloths or similar to prevent damage from subsequent exposure to the cleaning solution.

Caution: SC SCHATTEN is very strong and fast-acting! Neutralise with water at intervals if necessary to prevent surface damage!

Notes

Before use, test material compatibility in an inconspicuous area.

5 L canister | Order No. 30582



SC GEL EXTRA

Highly effective universal graffiti and dispersion paint remover



Field of Application

For graffiti removal on all substrates. SC GEL EXTRA is suitable for removing all common graffiti paints, particularly dispersion paint.

Product Properties

- NMP-/NEP-free
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- For removing spray paints based on nitro-combi, synthetic resin and acrylic, inks, and felt-tip pens, particularly effective against dispersion paints
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Consumption approx. 150 ml/m²
- Listed and approved in accordance with DB standard RIL 910
- Ready to use

Application

Apply SC GEL EXTRA undiluted, evenly and generously. Monitor the dissolving process. Once the dissolving process has begun, work on the graffiti with suitable mechanical means if necessary. Thoroughly remove the dissolved paint immediately. As a final step, rinse the cleaned surface thoroughly with plenty of water. Dry sensitive surfaces, such as paintwork, with absorbent cloths or similar after cleaning to prevent damage from subsequent exposure to the cleaner. Repeat the process as necessary until the desired result is achieved.

Notes

Before each application, test material compatibility in an inconspicuous area.

Box of 6 x 500 ml bottles | Order No. 00584

5 L canister | Order No. 30585

10 L bucket | Order No. 30579

SC SENSITIV

Graffiti remover for sensitive surfaces



Field of Application

For the gentle removal of graffiti caused by spray paints, inks and felt-tip pens from all sensitive and solvent-resistant substrates, paintwork and plastic surfaces, such as Plexiglas.

Product Properties

- NMP-/NEP-free
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- Highly effective against paint smears, graffiti and sticker residue on sensitive substrates
- Mild and gentle on surfaces
- Hazard-label-free (according to GHS)
- SC SENSITIV is ready to use and evaporates without residue
- Listed and approved in accordance with DB standard RIL 910

Application

Spray SC SENSITIV evenly onto a cloth and work over the surfaces to be cleaned. Monitor the dissolving process and remove the loosened paint by wiping with a scratch-free cloth. Repeat if necessary. **When using SC SENSITIV specifically on Plexiglas, do NOT wipe down with water afterwards – only remove residue with a scratch-free cloth or paper.** After using SC SENSITIV, no rinsing with water or neutralising of the surface is required. The product evaporates without residue.

Notes

Before first use, test compatibility in an inconspicuous area. Caution: Microfibres may cause scratches.

Box of 6 x 500 ml bottles | Order No. DRS00065

5 L canister | Order No. DRS00225



SC FASSADEN GEL

Powerful graffiti remover for buildings



Field of Application

For deep-penetrating graffiti and shadow removal on mineral substrates (e.g. concrete, clinker brick, brick), natural stone (e.g. granite, marble, limestone, sandstone, slate) and painted rendered surfaces on buildings.

Product Properties

- NMP-/NEP-free
- Orange terpene-free (significantly reduces the risk of allergic reaction)
- Suitable for combined use with other graffiti removers from the SC Anti-Graffiti System
- Barely runs on vertical surfaces thanks to gel formulation
- Highly alkaline
- Combined paint and shadow remover
- Also effective on wet substrates
- Consumption approx. 150 ml/m²
- Ready to use

Application

Graffiti removal with combined shadow removal: Apply SC FASSADEN GEL undiluted and evenly. Monitor the dissolving process. Absorb the dissolved paint immediately. Rinse thoroughly with water. Repeat the process as necessary until the desired result is achieved.

Caution: SC FASSADEN GEL is very strong and fast-acting! Neutralise with water at intervals if necessary to prevent surface damage!

Notes

Before each application, test material compatibility in an inconspicuous area.

10 L bucket | Order No. DRS01000

Personal contact, trustworthy collaboration.

Customer satisfaction is our main priority. The DR.SCHNELL service principle expresses our self-awareness as your partner. This includes a broad range of knowledge, expertise and easy access to your personal contact as well as certified theoretical and practical training.

We comprehensively support you so that you can take responsibility for cleanliness and hygiene in your field of work at all times. Our goal is for you to be able to use DR.SCHNELL products easily and safely in an environmentally friendly, sustainable and economical fashion.

Our service offer:

- Personal support from national key account managers and application engineers, as well as regional product specialists
- On-site analysis and concept creation for optimum cleaning processes
- Ensuring the preservation of vehicle and infrastructure through sustainable product solutions
- Cost control with concentration measurements of the detergents used on-site
- Support with special cleaning and problematic cases
- Theoretical and practical training on special topics such as graffiti removal and interior/exterior vehicle cleaning
- Practical training and continuing professional development, delivered on-site by ALEGRIA and online via the DR.SCHNELL CAMPUS

We're here for you – ONLINE & ON-SITE!



Change starts today.
For a better tomorrow.

DR.SCHNELL

DR.SCHNELL GmbH & Co. KGaA · Taunusstraße 19 · 80807 Munich
Tel. +49 (0) 89 / 350 60 80 · E-Mail: verkehrswesen@dr-schnell.de
Homepage: www.dr-schnell.com

DR.SCHNELL AG · Wülflingerstrasse 271 · CH-8408 Winterthur
Tel. +41 44 651 10 43 · E-Mail: ivr@dr-schnell.ch